

Air, fumes and dust




GAINE GA 1

+60
°C
-15

Flexible ducting in PVC for ventilation and fumes suction,

reinforced with a rigid PVC spiral.



- 1 Spiral in rigid PVC
- 2 Wall in soft blue PVC

APPLICATIONS

- Ventilation
- Suction of air and fumes

SECTORS OF ACTIVITY

- Industry

Marking : [batch number] Ø inn

ADVANTAGES

GA 1 is very light and high flexible. Its smooth inner wall assures low flow losses.

CONNECTORS

Connectors with wire collars or screwed fittings (left hand spiral).

CHEMICAL RESISTANCE

See table column A.

mm	± mm	mm	mm	g/m	mm	mm	Blue 30 m
20	+/- 0,8	0,5	2	110	300	20	190800
25	+/- 0,8	0,5	2	130	300	25	190813
30	+/- 0,8	0,5	2	150	300	30	190826
32	+/- 1	0,5	2	160	300	32	190900
35	+/- 1	0,5	2,25	180	300	35	190839
38	+/- 1	0,5	2,25	200	300	38	190913
40	+/- 1	0,5	2,4	210	200	40	190842
50	+/- 1,2	0,5	2,6	340	200	50	190855
60	+/- 1,2	0,5	3	400	200	60	190868
63	+/- 1,2	0,5	3	425	200	63	190926
76	+/- 1,4	0,5	3,4	530	200	76	190939
80	+/- 1,4	0,5	3,4	585	200	80	190884
102	+/- 1,6	0,5	3,8	820	100	102	190968